



## LUBRICANTS

POWER TO PERFORM

# HP X-3 30 KLT

Premium Quality Power Train Oil for  
KOMATSU Equipment

### DESCRIPTION

HP X-3 30 KLT grade is a premium quality Power Train Oil formulated from high quality hydro-treated base stocks and carefully selected additives, designed to meet the stringent Komatsu specifications.

HP X-3 30 KLT provides optimum protection against wear, rust & corrosion, and oxidation to swing machinery, damper case and final drive.

### APPLICATIONS

HP X-3 30 KLT grade is specifically designed to cater to stringent requirements of equipment manufactured by Komatsu. The product is approved by KOMATSU for their PC71, PC130-7, PC200-6, PC300-7, PC400-7 etc.

### FEATURES & BENEFITS

- Excellent Anti-wear performance for protection of final drives, gears and bearings
- Balanced friction coefficient to prevent overheating and thermal cracking of transmission clutch, brake, disks and plates
- Unmatched Anti-corrosion & ant-rust performance to ensure protection to critical components like bearings, gears and hydraulic pump components
- Good seal compatibility

### MEETS OR EXCEEDS REQUIREMENTS OF

- API CF
- KES 07.851
- KES 07.802

### PHYSICO-CHEMICAL PROPERTIES

Kinematic Viscosity @ 100°C, cSt, Min	9.0 – 13.0
Viscosity Index, Min	90
TBN, mg KOH/gm, Min	8.0
Flash Point, COC, °C, Min	200
Pour Point, °C, Max	-12